



### X124 Single Console

1920 x 1200  
WUXGA



### Drawer Features & Display Benefits

- ▶ 1U 24" widescreen LCD console drawer
- ▶ Support 1920 x 1200 native **WUXGA** Ultra high resolution
- ▶ PIP & Picture by Picture viewing efficiency
- ▶ Green LED-backlit panel technology
- ▶ 104-key keyboard with either touchpad or trackball
- ▶ MAC or SUN Micro keyboard options available
- ▶ New enhanced aesthetics with molded front handle
- ▶ Front USB port for device access ( USB Hub KVM only )

### Options

- 3G / HD / SD-SDI Broadcast-grade input ( w/ speaker )
- HDMI ( w/ speaker )
- DC power : 24V / 48V / 125V / 250V

Ordering Information	Standard ( left side open )	Option ( right side open )
Model	X124	X124R

### Specifications

#### • LCD Panel

Size (diagonal) :	24.1" Widescreen TFT
Max resolution :	1920 x 1200
Brightness (cd/m2) :	300
Backlight :	LED
Colors :	16.7 M
Contrast ratio (typ) :	1000 : 1
Viewing angle (H/V) :	178° x 178°
Active area (mm) :	518 x 324
MTBF (hrs) :	30,000
Video input :	Standard - DVI-D
( single only )	Option - HDMI ( bundle speaker x 2 )

#### • Speaker :

Built-in Dual Stereo Speakers  
( HDMI only ) 2W x 2

#### • Casing Color :

Black ( RAL 9005 )

#### • Power Input :

Auto-sensing 100 to 240VAC,  
50 / 60Hz

#### • Power Consumption ( single console )

Sreen on :	Max. 40W
Power saving mode :	Max. 5W
Power button on :	Max. 1W

#### • Environmental

Operating temperature :	0 to 55°C degree
Storage temperature :	-20 to 60°C degree
Operating humidity :	20~90%, non-condensing
Storage humidity :	5 ~90%, non-condensing
Operating altitude :	16,000 ft
Non-operating altitude :	40,000 ft
Shock :	10G acceleration ( 11ms duration )
Vibration :	5~500Hz 1G RMS random vibration

#### • Regulatory

Safety :	FCC & CE certified
Environmental :	RoHS2 & REACH compliant

#### • Weight ( single console )

Net :	15.3 kgs / 33.7 lbs
Gross :	19.5 kgs / 42.9 lbs

#### • Dimensions ( single console )

Product :	441.6 x 700 x 44 mm / 17.4 x 27.6 x 1.73 inch
Packing :	595 x 910 x 140 mm / 23.4 x 35.8 x 5.5 inch


### Console Cable

#### CX-6


- 6 feet DVI-D console cable ( bundle )
- DVI-D + USB, server end
  - DVI-D + DB15 ( USB KB & MS ), console port

### Standard Keyboard

**Ge** G keyboard integrated with touchpad



**Gb** G keyboard integrated with trackball



### Supporting layouts

<b>America</b>		United States								
<b>EMEA</b>		United Kingdom		Germany		France		Spain		Norway
		Italy		Russia		Switzerland		Netherlands		Portugal
<b>Asia</b>		China		Japan		Korea		Arabia		Turkey

### Keyboard Options

\* US layout only

**Me** Mac keyboard with touchpad



**Se** S keyboard with touchpad

**Mb** Mac keyboard with trackball

**Sb** S keyboard with trackball



# 1U 24" High Resolution LCD KVM Drawer



• **Dimensions ( with KVM )**

Product : 441.6 x 800 x 44 mm / 17.4 x 31.5 x 1.73 inch  
 Packing : 595 x 910 x 140 mm / 23.4 x 35.8 x 5.5 inch

• **Weight**

Net : 16.1 kgs / 35.4 lbs  
 Gross : 22 kgs / 48.4 lbs

• **Power Consumption with KVM integration :**

Screen on : Max. 65W  
 Power saving mode : Max. 30W

• **Casing Color :** Black ( RAL 9005 )

\* For details, please refer to our KVM rear kit user manuals.

[www.austin-hughes.com/support/usermanual/cyberview/UM-CV-MKVM-KIT.pdf](http://www.austin-hughes.com/support/usermanual/cyberview/UM-CV-MKVM-KIT.pdf)

For right side open - Add **R** at the end of the model no.  
 sample : X124-MIP1624R

Matrix DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	1	1	X124 - MIP813	X124 - MIP1613	-
	1	1	2	X124 - MIP824	X124 - MIP1624	-
	1	1	0	X124 - M802	X124 - M1602	-
	1	2	0	X124 - M803	X124 - M1603	-
	1	3	0	X124 - M804	X124 - M1604	-

[www.austin-hughes.com/support/usermanual/cyberview/UM-CV-SKVM-KIT.pdf](http://www.austin-hughes.com/support/usermanual/cyberview/UM-CV-SKVM-KIT.pdf)

Combo DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	0	1	X124 - IP802	X124 - IP1602	-
	1	1	0	X124 - 802	X124 - 1602	-
	1	0	0	X124 - S801	X124 - S1601	-

Combo DB-15 KVM Cable : CE-6 / 10 / 15 ( 6, 10 or 15 ft )

[www.austin-hughes.com/support/usermanual/cyberview/UM-CV-DVIKVM-KIT.pdf](http://www.austin-hughes.com/support/usermanual/cyberview/UM-CV-DVIKVM-KIT.pdf)

For right side open - Add **R** at the end of the model no.  
 sample : X124-1201DR

DVI-D KVM	Local	Remote	IP	12-port	-	-
	1	0	0	X124 - 1201D	-	-

DVI-D KVM Cable : CI-6 / 15 ( 6 or 15 ft )

[www.austin-hughes.com/support/usermanual/cyberview/UM-CV-USBKVM-KIT.pdf](http://www.austin-hughes.com/support/usermanual/cyberview/UM-CV-USBKVM-KIT.pdf)

For right side open - Add **R** at the end of the model no.  
 sample : X124-801HR

USB Hub DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	0	1	X124 - IP802H	X124 - IP1602H	-
	1	1	0	X124 - 802H	X124 - 1602H	-
	1	0	0	X124 - 801H	X124 - 1601H	-

USB KVM Cable : CB-6 / 10 / 15 ( 6, 10 or 15 ft )