

AP-20 6mm aluminum front bezel



Display Benefits

- 20" LCD with high resolution 1600 x 1200
- Rugged construction against external impact
- Protective 3mm glass

Options

- 3G / HD / SD-SDI Broadcast-grade input
- MCS Multi-display control solution
- Resistive (1-point touch)

(€ 🗸

- S-Video + Composite (BNC) or Audio input
- HDMI or DVI-D (either one for AV2.2 upgrade)

REACH

- MIL-type or lockable connector
- DC power: 12V / 24V / 48V / 125V / 250V
- Quad display for CCTV
- TV Analog

Basic I/O





AV3.0 upgrade I/O* with advanced features



*Casing dimensions will be changed

AV2.2D upgrade I/O



AV2.2H upgrade I/O



Specifications

• LCD Panel

1 LG Manufacturer: 20.1" TFT Size (diagonal):

Max resolution: 1600 x 1200

Brightness (cd/m2): 300 **CCFL** Backlight: Colors: 16.7 M Contrast ratio (typ): 800:1 Viewing angle (H/V): 178° x 178° Active area (mm): 408 x 306 MTBF (hrs): 45,000

Video input: VGA or DVI-D

Built-in Dual Stereo Speakers 2W x 2 Speaker:

(Bundled with AV2.2 upgrade)

• Power Input: Auto-sensing 100 to 240VAC, 50 / 60Hz

Power Consumption

Sreen on: Max. 48W Power saving mode: Max. 4W Power button on: Max. 1W

Environmental

Operating temperature: 0 to 55°C degree Storage temperature : -20 to 60°C degree Operating humidity: 20~90%, non-condensing Storage humidity: 5 ~90%, non-condensing

Operating altitude: 16,000 ft Non-operating altitude: 40,000 ft

Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration

• Casing Color: Black (RAL 9005)

Mounting : Panel mount / VESA mount

Regulatory

FCC & CE certified Safety:

Environmental: RoHS2 & REACH compliant


Weight

Net: 7 kgs / 15.4 lbs Gross: 9 kgs / 19.8 lbs

• Dimensions


Product: 512.5 x 72.1 x 391.6 mm / 20.2 x 2.8 x 15.4 inch Packing: 651 x 124 x 597 mm / 25.6 x 4.9 x 23.5 inch

Diagrams (mm)



Side View







NAP-20

NEMA 4 / IP65 front protection



Display Benefits

- 20" LCD with high resolution 1600 x 1200
- Rugged construction against external impact
- 6mm aluminum front bezel with protective glass & water proof sealed gasket

Options

F© (E 💆

- 3G / HD / SD-SDI Broadcast-grade input
- MCS Multi-display control solution
- Resistive (1-point touch)
- S-Video + Composite (BNC) or Audio input
- HDMI or DVI-D (either one for AV2.2 upgrade)

REACH

- MIL-type or lockable connector
- DC power: 12V / 24V / 48V / 125V / 250V
- Quad display for CCTV
- TV Analog

Basic I/O





AV3.0 upgrade I/O* with advanced features



*Casing dimensions will be changed

AV2.2D upgrade I/O



AV2.2H upgrade I/O



Specifications

• LCD Panel

(I) LG Manufacturer: 20.1" TFT Size (diagonal):

Max resolution: 1600 x 1200 Brightness (cd/m2): 300

CCFL Backlight: Colors: 16.7 M Contrast ratio (typ): 800:1 Viewing angle (H/V): 178° x 178° Active area (mm): 408 x 306 MTBF (hrs): 45,000

Video input: VGA or DVI-D

Built-in Dual Stereo Speakers 2W x 2 Speaker: (Bundled with AV2.2 upgrade)

• Power Input : Auto-sensing 100 to 240VAC, 50 / 60Hz

Power Consumption

Sreen on: Max. 48W Power saving mode: Max. 4W Power button on: Max. 1W

Environmental

Operating temperature: 0 to 55°C degree Storage temperature : -20 to 60°C degree Operating humidity: 20~90%, non-condensing Storage humidity: 5 ~90%, non-condensing

Operating altitude: 16,000 ft Non-operating altitude: 40,000 ft

Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration

• Casing Color: Black (RAL 9005)

• Mounting: Panel mount / VESA mount

Regulatory

Safety: FCC & CE certified

Environmental: RoHS2 & REACH compliant


Weight

Net: 7 kgs / 15.4 lbs 9 kgs / 19.8 lbs Gross:

Dimensions

Product: 512.5 x 72.1 x 391.6 mm / 20.2 x 2.8 x 15.4 inch Packing: 651 x 124 x 597 mm / 25.6 x 4.9 x 23.5 inch

Diagrams (mm)



Side View

