

OP-X17 Universal open frame mounting




Display Benefits

- ▶ 17" widescreen LCD with 1920 x 1200 native **WUXGA** Ultra high resolution
- ▶ Standard with HDMI, DVI-D, VGA, S-Video, BNC, Audio & remote controller
- ▶ PIP & Picture by Picture viewing efficiency
- ▶ Green LED-backlit panel technology
- ▶ Rugged construction against external impact

Options

- 3G / HD / SD-SDI Broadcast-grade input
- **MCS** Multi-display control solution
- Resistive / Capacitive (1-point touch)
- MIL-type or lockable connector
- DC power : 12V / 24V / 48V / 125V / 250V

Basic I/O



Specifications

• LCD Panel

Size (diagonal) :	17.1" Widescreen TFT
Max resolution :	1920 x 1200
Brightness (cd/m2) :	210
Backlight :	LED
Colors :	16.7 M, 8-bit
Contrast ratio (typ) :	600 : 1
Viewing angle (H/V) :	130° x 110°
Active area (mm) :	367 x 230
MTBF (hrs) :	20,000
Video input :	HDMI / DVI-D / VGA / S-Video / BNC

• Speaker :

Built-in Dual Stereo Speakers
2W x 2

• Power Input :

Auto-sensing 100 to 240VAC, 50 / 60Hz

• Power Consumption

Screen on :	Max. 34W
Power saving mode :	Max. 4W
Power button on :	Max. 1W

• Environmental

Operating temperature :	0 to 55°C degree
Storage temperature :	-20 to 60°C degree
Operating humidity :	20~90%, non-condensing
Storage humidity :	5 ~90%, non-condensing
Operating altitude :	16,000 ft
Non-operating altitude :	40,000 ft
Shock :	10G acceleration (11ms duration)
Vibration :	5~500Hz 1G RMS random vibration

• Casing Color :

Black (RAL 9005)

• Mounting :

Universal mount / VESA mount

• Regulatory

Safety :	FCC & CE certified
Environmental :	RoHS2 & REACH compliant

• Weight

Net :	3.8 kgs / 8.4 lbs
Gross :	6.5 kgs / 14.3 lbs

• Dimensions

Product :	465.5 x 50.6 x 328 mm / 18.3 x 2 x 12.9 inch
Packing :	615 x 113 x 523 mm / 24.2 x 4.4 x 20.6 inch

Diagrams (mm)

