Combo DB-15 KVM

CyberView™

Benefits

- **DB-15 KVM with 8 or 16 ports in 1U**
- **Local console & KVM ports support resolution up to 1920 x 1200**
- **Multi-platform for PC, server, Blade Server & SUN / MAC**
- **Port switching via OSD, front button & keyboard hotkeys**
- **Multi lingual OSD menu**
- **Hot pluggable, no software or drivers required**
- **Cascade levels up to 8 KVM switches**
- **TAA Compliant**

Options

- DC power options : 12V / 24V / 48V / 125V

Basic Models - local console x 1



CV-S801



CV-S1601

KVM Port	
Port # :	8 or 16
Connector :	DB-15
Connectivity :	VGA + USB KB / MS 2-in-1 KVM cable (6 / 10 / 15 feet)
Resolution :	16:9 - max. 1920 x 1080 / 16:10 - max. 1920 x 1200 / 4:3 - max. 1600 x 1200

Local Console	
Graphic Connector :	1 x DB-15 VGA
Input device :	2 x USB type A for keyboard & mouse
Resolution :	16:9 - max. 1920 x 1080 / 16:10 - max. 1920 x 1200 / 4:3 - max. 1600 x 1200

IP Models - local console + IP console



IP-802



IP-1602

IP Console	
Connector :	RJ45
User management :	1 x active user, 15-user login
Network protocol :	DHCP / BOOTP / DNS
Security :	TLS 1.3, AES, LDAP, Active Directory (AD), HTTP(s)
Browser :	Chrome, Firefox, Edge, etc.
Resolution :	16:9 - max. 1920 x 1080 / 16:10 - max. 1920 x 1200 / 4:3 - max. 1600 x 1200



High Performance KVM Access Over IP

Remote Models - local console + remote console



CV-802



CV-1602

Remote Console	
Connector :	RJ45
Connection :	via Cat5 / Cat6 cable to receiver box
Receiver box I/O :	VGA + 2 x USB type A for keyboard & mouse
Resolution :	16:9 - (1920 x 1080) Max. 50 meters 16:10 - (1920 x 1200) Max. 50 meters 16:10 - (1440 x 900) Max. 100 meters 4:3 - (1600 x 1200) Max. 100 meters 4:3 - (1280 x 1024) Max. 150 meters

Receiver box

Copyright 2026 Austin Hughes Electronics Ltd. All rights reserved.

Local console & KVM port connection

CB - 6 / 10 / 15
6 / 10 / 15 ft USB KVM cable



IP console connection



Remote console connection



KVM Cascade

- 8-level cascade up to 128 servers
- KVM cascade via CBC-6
- Level 2 - 8 KVM must be basic models :
  CV-S801 / CV-S1601
- 1st level KVM takes all control of slave KVMs



Management	
Port switching	OSD, front button & keyboard hotkeys
Expansion	8-level cascade up to 128 servers

Power	
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz
Consumption	Max. 19W

Compatibility	
Hardware	HP / IBM / Dell PC, Server and Blade Server SUN / Mac
OS support	Windows / Linux / Unix / Mac OS

Compliance	
EMC	FCC & CE
Safety	CE / LVD & UKCA
Environment	REACH & RoHS3 / WEEE

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	10~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Physical		
Product (W x D x H)		443 x 171 x 44 mm 17.4 x 6.7 x 1.73 inch
Packing (W x D x H)		500 x 400 x 140 mm 19.7 x 15.8 x 5.5 inch
Weight	Net	2.6 kg / 5.7 lb
	Gross	4.2 kg / 9.2 lb
Chassis color		Dark
Chassis materials		Steel

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication. All brand names, logo and registered trademarks are properties of their respective owners.

Copyright 2026 Austin Hughes Electronics Ltd. All rights reserved.