



Top View

Front Door  
Cool Air InRear Door  
Hot Air Out**Benefits**

- ▶ Easy installation with common tools
- ▶ Thin & light weight design only 5 kgs / 11 lbs
- ▶ Designed for low noise & high airflow performance
- ▶ Improves extraction of heat from high density rack
- ▶ Cascade ports for daisy chain up to 16 levels via Cat6 cable
- ▶ 1 x intelligent master fan unit allows access to 16 fan unit levels over internet
- ▶ Free **ICM-02** management software remote access up to 480 fan units
- ▶ Auto & manual CFM setting reduces power consumption
- ▶ 1 x bundled temp. sensor with 2M wire
- ▶ Temperature sensing technology adjusts the fan speeds accordingly
- ▶ Unit or individual fan on / off ( remote or local )
- ▶ 48V, 24V or 12VDC power option
- ▶ TAA Compliant

Model	Installation	Airflow	Purpose
RF-33.9A	Rear door outside	Extract airflow	Exhaust air out from rack
	Front door inside	Intake airflow	Cool air in from aisle
RF-33.9B	Front door outside	Intake airflow	Cool air in from aisle
	Rear door inside	Extract airflow	Exhaust air out from rack

\* Package includes the material of clear polycarbonate plastic to block off the remaining open perforated area of the door to eliminate bypass air.

**Product Specifications**

RF-33.9A / RF-33.9B	
No. of Fan	9
Mounting	Door Mount
CFM Level	Normal / High / Max.
Individual Fan ON / OFF	Yes
Individual Fan CFM	108 CFM
Unit CFM ( approx. )	972 CFM
IP Remote Access	Not available, must be via Intelligent ( Master ) Fan on level 1
Daisy Chain Level	for level 2 - 16
MTBF	50,000 hrs
Individual Fan Noise Level	41 dB

Temperature Sensor	
Temperature Port	1 x temperature sensor port ( sensor bundled )
Measurement Range	0 to 99.9°C
Measurement Accuracy	+/- 1.5%
Temperature Alarm	Yes

Power	
Consumption	Auto-sensing 100V or 240V AC at 50 or 60Hz via IEC cord
Consumption	60W

Environment	
Operating / Storage	0 to 50°C / -5 to 60°C
Relative Humidity	90%, non-condensing
Shock	50G acceleration ( 11ms, half-sine wave )
Vibration	58~100Hz / 0.98G ( 11ms / cycle )

Physical		
Dimensions ( W x D x H )	Product	195 x 43 x 1466 mm / 7.7 x 1.7 x 57.7 inch
	Packing	263 x 106 x 1650 mm / 10.4 x 4.2 x 65 inch
Weight	Net / Gross	5 kg ( 11 lb ) / 7.4 kg ( 16.3 lb )
Casing Color		Black

Compliance	
EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS3 & REACH compliant