


### Broadest Portfolio of 3-Phase PDU




Austin Hughes offers cost efficient PDU models with most popular configurations in the market. In addition, custom PDU configurations are also available on request for flexibility & specific user requirements. With build to order system, we produce & deliver exactly what customer needs.

### > Quality PDUs in Short Lead Time



Austin Hughes designs highly reliable 3-Phase PDUs in efficient production, assembly and inventory process. Every InfraPower PDU unit is 100% tested before shipment. All these efforts allow us to deliver quality PDUs to customers in the shortest lead time.

#### > 1U / 2U Rackmount



These days, many 19" rack mount 3-Phase PDUs with high density circuits are specified as being 2U in height.

Apart from 2U, InfraPower offers 1U rackmount PDU solution when rack space is at a premium.

### > Compliance Approval



Our dedicated PDU compliance team ensures conformance to safety & reliability standard in US, EMEA & APAC.

### > Circuit Protection



Safety operation is essential for your data center and server room. InfraPower 3-Phase PDU applies Hydraulic MCB to protect the PDU circuit from current overload.

### > Lockable / Fused IEC Outlet PDU



Specific IEC outlet configurations available on request.

Lockable IEC Outlet PDU models secure plugs and prevent accidental disconnection. Individually fused outlets help prevent an overload of the active equipment.

### **208V PDU**

Outlet nos		2007 004/004	Rack U	
C13	C19	208V - 20A/30A	Nack U	
21	3	HP21C13 / 3C19	2U	
18	6	HP18C13 / 6C19	2U	
24		HP24C13	2U	
18		HP18C13	2U	
	18	HP18C19	2U	

### **400V PDU**

Outlet nos		4007 404 (004	Rack U	
C13	C19	400V - 16A/32A	Nack U	
21	3	HP21C13 / 3C19	2U	
18	6	HP18C13 / 6C19	2U	
6	3	HP6C13 / 3C19	1U	
24		HP24C13	2U	
18		HP18C13	2U	
12		HP12C13	1U	
	18	HP18C19	2U	
	9	HP9C19	1U	



Inlet		Amp	Cordset	
met		Allip	AWG	length
	60309	60A	6	6.6 FT
208V	© CS8365C	50A	6	6.6 FT
200V	L15-30P L21-30P	30A	10	6.6 FT
	£ L15-20P	20A	12	6.6 FT
Inlet	Inlat		Cordset	
met		Amp	mm²	length
	60309	63A	10	2 M
400V	60309	32A	4	2 M
	60309	16A	1.5	2 M

Available for : - Custom PDU

- Colored Chassis & IEC Outlet
- Lockable or Individually Fused IEC outlet PDU
- 400V 63A & 208V 50A / 60A PDU Configurations

# **Accessories**

### **Colored PDU Chassis**

 Colored PDU chassises allow easy identification of power paths and manageability of power sources.

Standard color: Black
Optional color: Red, Blue, White,
Green, Orange, Yellow, Purple



### **Colored IEC Outlet**

 Colored C13 & C19 outlets visualize power connection of IT devices and hence facilitate power distribution management.

 $\textbf{Standard color}: \textcolor{red}{\textbf{Red}}, \textcolor{red}{\textbf{Blue}}, \textcolor{blue}{\textbf{White}}$ 

Optional color : Black



## **Colored Power Cords**

 Enhance cable management and visualize power sources

C13 - C14 6ft ( 1.0 mm² )
- Blue / Red / Orange / Light Grey
C19 - C20 6ft ( 1.5 mm² )
- Blue / Red
C13 - C14 10ft ( 1.0 mm² )
- Blue / Red / Orange / Light Grey



## **IEC Secure Sleeves**

Sleeve attached to C14 power cord inlet: IPP-SS-C13 ( pack of 200 )

Sleeve attached to C20 power cord inlet: IPP-SS-C19 ( pack of 100 )

- Secure the power cord connections to the PDU IEC outlets
- Simple and cost efficient



IPP-SS-C13 IPP-SS-C19