


1-Phase Dual Feed Metered PDU specification drawing

230V 16A / 20A / 32A PDU : C13 x 32



32A model :	Circuit Protection
DV32C13-32A-MD/ F _EN/3 B -1	Resettable Fuse x 4
DV32C13-32A-MD/ CR _EN/3 T -1	1-pole MCB x 4

Input Rating : 32Amp, 230V
Cordset : 3 meter 4.0mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 4
PDU I : < **Circuit A** > Output 16A max., C13 #1-8
< **Circuit B** > Output 16A max., C13 #9-16
PDU II : < **Circuit A** > Output 16A max., C13 #1-8
< **Circuit B** > Output 16A max., C13 #9-16
Weight : Net 12.5 kg / Gross 14.5 kg



20A model :	Circuit Protection
DV32C13-20A-MD/ F _OE/3 B -1	Resettable Fuse x 2
DV32C13-20A-MD/ CR _OE/3 T -1	1-pole MCB x 2

Input Rating : 20Amp, 230V
Cordset : 3 meter 2.5mm sq. H05V V-F cordset
Protection : 20A resettable fuse or 20A hydraulic MCB x 2
PDU I : Output 20A max., C13 #1-16
PDU II : Output 20A max., C13 #1-16
Weight : Net 12.5 kg / Gross 14.5 kg



16A model :	Circuit Protection
DV32C13-16A-MD/ F _EN/3 B -1	Resettable Fuse x 2
DV32C13-16A-MD/ CR _EN/3 T -1	1-pole MCB x 2

Input Rating : 16Amp, 230V
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 2
PDU I : Output 16A max., C13 #1-16
PDU II : Output 16A max., C13 #1-16
Weight : Net 12.5 kg / Gross 14.5 kg



16A model :	Circuit Protection
DV32C13-16A-MD/ F _C20/3 B -1	Resettable Fuse x 2
DV32C13-16A-MD/ CR _C20/3 T -1	1-pole MCB x 2

Input Rating : 16Amp, 230V
Cordset : 3 meter 1.5mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 2
PDU I : Output 16A max., C13 #1-16
PDU II : Output 16A max., C13 #1-16
Weight : Net 12.5 kg / Gross 14.5 kg

Operating Temperature : -5 to 60 °C
Storage Temperature : -25 to 65 °C
Operating Altitude : 0 to 2,000 m
Storage Altitude : 0 to 15,000 m
Humidity : 8 to 95% RH, non-condensing

Meter Features (MD metered PDU)
Local Display : 3-digit LED ammeter measuring input load current
Measurement : Current (A)
Accuracy : ± (3% of the reading + 5 digits) RMS

EMC Compliance : CE / EMC
Safety Compliance : CE / LVD & UKCA
Tested to EN 62368-1:2014 / A11:2017 standard
Tested to EN 60730-1:2016 / A1:2019 standard
Environment Compliance : RoHS3 & REACH

AUSTIN HUGHES
Design. Manufacturing. Global Services.

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

Copyright 2023 Austin Hughes Electronics Ltd. All rights reserved.

Product Dimension : 82 (W) x 70 (D) x 1500 (H) mm
Packing dimension : 110 (W) x 268 (D) x 1793 (H) mm