


3-Phase monitored PDU specification drawing

400V 16A / 32A PDU : C13 x 36 + C19 x 12

unit : mm



| Circuit Protection | Code |
|--------------------|------|
| Fuse               | F    |
| MCB                | CR   |



| 32A model :                                      | Circuit Protection  |
|--------------------------------------------------|---------------------|
| VP36C13/12C19-32A-W/ <b>F</b> _EN/2 <b>B</b> -1  | Resettable Fuse x 6 |
| VP36C13/12C19-32A-W/ <b>CR</b> _EN/2 <b>T</b> -1 | 1-pole MCB x 6      |

- Input Rating : 32Amp, 400V 3PH  
Cordset : 5-wire 2 meter 4mm sq. H05V V-F cordset  
Protection : 16A resettable fuse or 16A single pole hydraulic MCB x 6  
PH-1 - Bank 1 : Output 16A max., C13 #1-11 (odd) + C19 #C1,C3  
Bank 2 : Output 16A max., C13 #2-12 (even) + C19 #C2,C4  
PH-2 - Bank 3 : Output 16A max., C13 #1-11 (odd) + C19 #C1,C3  
Bank 4 : Output 16A max., C13 #2-12 (even) + C19 #C2,C4  
PH-3 - Bank 5 : Output 16A max., C13 #1-11 (odd) + C19 #C1,C3  
Bank 6 : Output 16A max., C13 #2-12 (even) + C19 #C2,C4  
Weight : Net 12.20 Kg / Gross 14.20 Kg

| PDU Feed | Code |
|----------|------|
| Bottom   | B    |
| Top      | T    |

| Chassis Color | Code |
|---------------|------|
| Black         | 1    |
| White         | 2    |
| Red           | 3    |
| Blue          | 4    |
| Green         | 5    |
| Orange        | 6    |
| Yellow        | 7    |
| Purple        | 8    |



| 16A model :                                      | Circuit Protection  |
|--------------------------------------------------|---------------------|
| VP36C13/12C19-16A-W/ <b>F</b> _EN/2 <b>B</b> -1  | Resettable Fuse x 3 |
| VP36C13/12C19-16A-W/ <b>CR</b> _EN/2 <b>T</b> -1 | 1-pole MCB x 3      |

- Input Rating : 16Amp, 400V 3PH  
Cordset : 5-wire 2 meter 1.5mm sq. H05V V-F cordset  
Protection : 16A resettable fuse or 16A single pole hydraulic MCB x 3  
PH-1 : Output 16A max., C13 #1-12 + C19 #C1-C4  
PH-2 : Output 16A max., C13 #1-12 + C19 #C1-C4  
PH-3 : Output 16A max., C13 #1-12 + C19 #C1-C4  
Weight : Net 12.20 Kg / Gross 14.20 Kg

Standard color : Black

- Operating Temperature : -5 to 60 °C  
Storage Temperature : -25 to 65 °C  
Operating Altitude : 0 to 2,000 m  
Storage Altitude : 0 to 15,000 m  
Humidity : 8 to 95% RH, non-condensing

**AUSTIN HUGHES**  
Design. Manufacturing. Global Services.

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

Copyright 2023 Austin Hughes Electronics Ltd. All rights reserved.

- Meter Features ( W Monitored PDU )**  
Local Display : Field replaceable 2.8" color LCD with touchscreen  
Bank Measurement : Current ( A ), Energy ( kWh ), Voltage ( V ) & Power factor  
Accuracy : ±1% Billing-grade  
IP Access : via IP dongle, one IP Access up to 32 PDU Levels  
Cascade : Up to 32 PDU under single IP address via IP dongle  
SNMP : V2 / V3 via IP dongle  
Sensor Port x 2 : Temp. Sensor / Temp. + Humid. Sensor


- IP dongle ( option )**  
- Dual LAN Network Failover  
- 10/100 Ethernet & Gigabit Ethernet standard  
- Enterprise IP Authentication, LDAPv3 / LDAPS, Active Directory®, RADIUS protocol

- EMC Compliance : CE / EMC  
Safety Compliance : CE / LVD & UKCA  
Tested to EN 62368-1:2014 / A11:2017 standard  
Tested to EN 60730-1:2016 / A1:2019 standard  
Environment Compliance : RoHS3 & REACH


- Product Dimension : 85 (W) x 90 (D) x 1850 (H) mm  
Packing dimension : 110 (W) x 268 (D) x 2168 (H) mm

Lockable IEC Outlet

- Patented design for InfraPower PDU



C13 Outlet



C19 Outlet


Lockable IEC Cable

- Patented design of InfraPower PDU
- Low cost, easy to lock & secure
- Proprietary for lockable IEC outlet
- Applicable to standard IEC outlet
- 6 colors & 3 lengths available
- Custom color & length on request
- VDE & ENEC approval

C13 - C14

H05VV-F 3G 0.75mm²


| Cable Color | 0.5M | 1M | 2M |
|-------------|------|----|----|
| Black       | ✓    | ✓  | ✓  |
| Grey        | ✓    | ✓  | ✓  |
| Red         | ✓    | ✓  | ✓  |
| Blue        | ✓    | ✓  | ✓  |
| Green       | ✓    | ✓  | ✓  |
| Orange      | ✓    | ✓  | ✓  |



C19 - C20

H05VV-F 3G 1.5mm²

| Cable Color | 1M | 2M |
|-------------|----|----|
| Black       | ✓  | ✓  |
| Grey        | ✓  | ✓  |
| Red         | ✓  | ✓  |
| Blue        | ✓  | ✓  |
| Green       | ✓  | ✓  |
| Orange      | ✓  | ✓  |




C13 - C14




lockable cable

C19 - C20

- ✓ low cost
- ✓ easy to lock
- ✓ secure



### VMS Mounting Button



### VMB Mounting Bracket

