




Benefits

- ▶ 1U 17" 4K LED-backlit LCD console drawer
- ▶ Dual slide - LCD and keyboard slide independently
- ▶ 3840 x 2160@60Hz native resolution / 16.7M colors (8-bit)
- ▶ 2560 x 1440 @60Hz QHD resolution support
- ▶ 1920 x 1080 & 1920 x 1200 resolution support
- ▶ 104-key USB keyboard with touchpad
- ▶ Display port 1.2 video input / USB KB/MS
- ▶ Built-in dual stereo speakers
- ▶ One Man installation design
- ▶ Enhanced aesthetics with molded front handle and two point lock
- ▶ 2-year standard warranty (upgradable up to 5 years)
- ▶ TAA Compliant

Options

- HDMI 2.0 video input (**HDMI**)
- 3G / HD / SD-SDI Broadcast-grade input (**SDI**)
- DC power : 12V / 24V / 48V / 125V / 250V
- SUN Micro keyboard option



Product Specifications

Console Port

Video input attached 6ft DP cable	Display port 1.2
KB / MS bundled 6ft USB cable x 2	USB type A

Video Option

Digital	HDMI	HDMI 2.0 / HDCP 2.2
---------	------	---------------------

LED-backlit LCD Panel

Panel size (diagonal)	17.3"
Native resolution	3840 x 2160@60Hz
Brightness (cd/m ²)	400
Contrast ratio (typ.)	1000 : 1
Colors	16.7 M, 8-bit
Viewing angle (L/R/U/D)	89/89/89/89
Response time (ms)	16
Dot pitch (mm)	0.0995
Display area (mm)	382.12H x 214.94V
Surface treatment	Anti-glare
Surface hardness	3H
Backlight type	LED
MTBF (hrs)	15,000

Power

Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 35W / Max. 52W
	Power saving mode	Max. 2W / Max. 18W
	Power button off	Max. 1W / Nil

Physical

Product (W x D x H)	Single console	442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch
	Console w/ KVM	442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch
Packing (W x D x H)	Single console /	590 x 815 x 140 mm
	Console w/ KVM	23.2 x 32.1 x 5.5 inch
Net weight	Single console	12 kg / 26.4 lb
	Console w/ KVM	13 kg / 28.6 lb
Gross weight	Single console	18 kg / 39.6 lb
	Console w/ KVM	19 kg / 41.8 lb

* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Environment

Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	10~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Mounting Distance

Single console drawer / Console w/ KVM drawer	660 ~ 870 mm 26 ~ 34.3 inch
--	--------------------------------


Compliance

EMC	FCC & CE
Safety	CE / LVD & UKCA
Environment	REACH & RoHS3 / WEEE

DK117 models w/ KVM

4K 60Hz KVM	IP	Remote	8-port
	0	0	DK117 - 801K

back




** Resolution related to LED-backlit LCD specification

4K KVM Cable	
CK - 6P (6 ft) DP KVM cable	CK - 6H (6 ft) HDMI KVM cable
Resolution	16:9 - max. 3840 x 2160
Support ** :	16:10 - max. 1920 x 1200
	4:3 - max. 1600 x 1200

Standard Keyboard

Ge G keyboard with touchpad



Supporting layouts

- America** U.S.
- EMEA** U.K. Germany France Russia Spain Italy
- Asia** Japan Korea

Keyboard Options

* US layout only

Se S keyboard with touchpad

