




Benefits

- ▶ 2U 17" 4K LED-backlit LCD console drawer
- ▶ Dual slide - LCD and keyboard slide independently
- ▶ 3840 x 2160@60Hz native resolution / 16.7M colors (8-bit)
- ▶ 2560 x 1440@60Hz QHD resolution support
- ▶ 1920 x 1080 & 1920 x 1200 resolution support
- ▶ Display port 1.2 video input / USB KB/MS
- ▶ 104-key USB keyboard with either touchpad or trackball
- ▶ Built-in dual stereo speakers
- ▶ Short depth design of 480mm
- ▶ One Man installation design
- ▶ Enhanced aesthetics with molded front handle and two point lock
- ▶ 2-year standard warranty (upgradable up to 5 years)
- ▶ TAA Compliant

Options

- HDMI 2.0 video input (**HDMI**)
- 3G / HD / SD-SDI Broadcast-grade input (**SDI**)
- DC power : 12V / 24V / 48V / 125V / 250V
- SUN Micro keyboard option
- Touchscreen : Projected Capacitive 10-pt / Resistive 1-pt



Product Specifications

Console Port	
Video input attached 6ft DP cable	Display port 1.2
KB / MS bundled 6ft cable : USB x 2	USB type A

Video Option		
Digital	HDMI	HDMI 2.0 / HDCP 2.2

LED-backlit LCD Panel	
Panel size (diagonal)	17.3"
Native resolution	3840 x 2160@60Hz
Brightness (cd/m ²)	400
Contrast ratio (typ)	1000 : 1
Colors	16.7 M, 8-bit
Viewing angle (L/R/U/D)	89/89/89/89
Response time (ms)	16
Dot pitch (mm)	0.0995
Display area (mm)	382.12H x 214.94V
Surface treatment	Anti-glare
Surface hardness	3H
Backlight type	LED
MTBF (hrs)	15,000

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 35W / Max. 52W
	Power saving mode	Max. 2W / Max. 18W
	Power button off	Max. 1W / Nil

Physical			
Product (W x D x H)	Single console	442 x 480 x 88 mm	17.4 x 18.9 x 3.5 inch
	Console w/ KVM	442 x 480 x 88 mm	17.4 x 18.9 x 3.5 inch
Packing (W x D x H)	Single console /	585 x 620 x 190 mm	23 x 24.4 x 7.5 inch
	Console w/ KVM	585 x 620 x 190 mm	23 x 24.4 x 7.5 inch
Net weight	Single console	20.4 kg / 44.9 lb	
	Console w/ KVM	21.1 kg / 46.4 lb	
Gross weight	Single console	24.8 kg / 54.6 lb	
	Console w/ KVM	27 kg / 59.4 lb	


* All dimensions stated are subject to change if options are selected / integrated to base model part codes


Mounting Distance	
Single console drawer /	490 ~ 700 mm
Console w/ KVM drawer	19.3 ~ 27.6 inch

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	10~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Compliance	
EMC	FCC & CE
Safety	CE / LVD & UKCA
Environment	REACH & RoHS3 / WEEE

RKP2417K models w/ KVM



HDMI KVM	 Remote	8-port
	0	0



back





** Resolution related to LED-backlit LCD specification


HDMI KVM Cable	
	
CK - 6P (6 ft) DP KVM cable	CK - 6H (6 ft) HDMI KVM cable
Resolution	16:9 - max. 3840 x 2160
Support ** :	16:10 - max. 1920 x 1200
	4:3 - max. 1600 x 1200

Standard Keyboard









Ge G keyboard with touchpad



Gb G keyboard with trackball



Supporting layouts

America		U.S.
EMEA	    	U.K. Germany France Spain Italy
Asia	 	Japan Korea

Keyboard Options

* US layout only

Se S keyboard with touchpad



Sb S keyboard with trackball