



### Benefits

- ▶ 1U 20" LCD display drawer
- ▶ 1152 x 900 SUN Micro resolution / 16.7M colors
- ▶ HDMI 1.4 + VGA video input ( speakers excluded )
- ▶ Short depth design of 500mm
- ▶ One Man installation design
- ▶ Enhanced aesthetics with molded front panel and two point lock
- ▶ 2-year standard warranty ( upgradable up to 5 years )
- ▶ TAA Compliant

### Options

- DC power : 12V / 24V / 48V / 125V / 250V

## Product Specifications

Video	
Video input	HDMI 1.4 + VGA

Compliance	
EMC	FCC & CE
Safety	CE / LVD & UKCA
Environment	REACH & RoHS3 / WEEE

LCD Panel		
Panel size ( diagonal )	20.1"	
Resolution	Direct	1152 x 900
	Native	1600 x 1200
Brightness ( cd/m <sup>2</sup> )	300	
Contrast ratio ( typ. )	800 : 1	
Colors	16.7 M	
Viewing angle ( L/R/U/D )	89/89/89/89	
Response time ( ms )	16	
Dot pitch ( mm )	0.255	
Display area ( mm )	408H x 306V	
Surface treatment	Anti-glare, Hard-coating	
Surface hardness	3H	
Backlight type	CCFL	
MTBF (hrs)	45,000	

Mounting Distance	
Display drawer	660 ~ 890 mm 26 ~ 35 inch

Physical		
Dimensions ( W x D x H )	Product	440 x 650 x 44 mm 17.3 x 25.6 x 1.73 inch
	Packing	595 x 815 x 140 mm 23.4 x 32.1 x 5.5 inch
Weight	Net	13.5 kg / 29.7 lb
	Gross	17.5 kg / 38.5 lb

\* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption	Screen on	Max. 45W
	Power saving mode	Max. 2W
	Power button off	Max. 1W

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	10~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration ( 11ms duration )
Vibration	10~300Hz 0.5G RMS random vibration

### Diagrams ( mm )

