



<b>16A model :</b>	<b>Circuit Protection</b>
MiniBoot-D8C13-16A / 208V	16A resettable fuse x 2

Input Rating : 16Amp, 208V  
 Outlet : C13 #1-8  
 Inlet : 16A IEC320 C20 x 2  
 Protection : 16A resettable fuse x 2  
 Circuit : < PDU A > C13 #1-4 / Output 12A max.  
 < PDU B > C13 #1-4 / Output 12A max.



**Meter Features ( MiniBoot PDU )**

Local Display	: 3-digit LED ammeter for input current
Measurement	: Current ( Amp )
Alarm threshold support	: Overload, temp, humidity & auto-ping
Remote management	: Telnet or SNMP v2 / v3
Outlet	: ON / OFF / Reboot over network
IP security	: LDAPv3 / LDAPS, AD, RADIUS, local credential database
Protocol	: HTTP(S), SSH Command Line Interface, Telnet, SMTP, IPv6/IPv4
1 x IP port	: 10 / 100 / 1000 Base T, RJ45
1 x serial port	: for CLI command access
2 x sensor port	: Support Temp. / Temp. + Humid. / Smoke sensor / Door switch
1 x USB port	: for Wifi Kit ( option )

Chassis Material	: Steel
Chassis Color	: White
Net weight	: 4.0 lb
Gross wieht	: 6.2 lb
Product Dimension	: 17.2 (W) x 5.5 (D) x 1.8 (H) inch
Packing dimension	: 20.7 (W) x 9.1 (D) x 3.1 (H) inch

EMC Compliance	: FCC Part 15 Subpart B
Safety Compliance	: UL 62368-1:2014
Environment Compliance	: RoHS3, Reach & WEEE
Operating Temperature	: -5 to 60 °C
Storage Temperature	: -25 to 65 °C
Operating Altitude	: 0 to 2,000 m
Storage Altitude	: 0 to 15,000 m
Humidity	: 8 to 95% RH, non-condensing