



16A model :	Circuit Protection
MiniBoot-D8C13-16A / 230V	16A resettable fuse x 2

Input Rating : 16Amp, 230V
 Outlet : C13 #1-8
 Inlet : 16A IEC320 C20 x 2
 Protection : 16A resettable fuse x 2
 Circuit : < PDU A > C13 #1-4 / Output 16A max.
 < PDU B > C13 #1-4 / Output 16A max.

13A model :	Circuit Protection
MiniBoot-D8C13-13A / 230V	13A resettable fuse x 2

Input Rating : 13Amp, 230V
 Outlet : C13 #1-8
 Inlet : 16A IEC320 C20 x 2
 Protection : 13A resettable fuse x 2
 Circuit : < PDU A > C13 #1-4 / Output 13A max.
 < PDU B > C13 #1-4 / Output 13A max.

10A model :	Circuit Protection
MiniBoot-D8C13-10A / 230V	10A resettable fuse x 2

Input Rating : 10Amp, 230V
 Outlet : C13 #1-8
 Inlet : 16A IEC320 C20 x 2
 Protection : 10A resettable fuse x 2
 Circuit : < PDU A > C13 #1-4 / Output 10A max.
 < PDU B > C13 #1-4 / Output 10A max.



Meter Features (MiniBoot PDU)

Local Display	: 3-digit LED ammeter for input current
Measurement	: Current (Amp)
Alarm threshold support	: Overload, temp, humidity & auto-ping
Remote management	: Telnet or SNMP v2 / v3
Outlet	: ON / OFF / Reboot over network
IP security	: LDAPv3 / LDAPS, AD, RADIUS, local credential database
Protocol	: HTTP(S), SSH Command Line Interface, Telnet, SMTP, IPv6/IPv4
1 x IP port	: 10 / 100 / 1000 Base T, RJ45
1 x serial port	: for CLI command access
2 x sensor port	: Support Temp. / Temp. + Humid. / Smoke sensor / Door switch
1 x USB port	: for Wifi Kit (option)

Chassis Material	: Steel
Chassis Color	: White
Net weight	: 1.8 kg
Gross wieht	: 2.8 kg
Product Dimension	: 437.5 (W) x 140 (D) x 44.5 (H) mm
Packing dimension	: 525 (W) x 230(D) x 80 (H) mm

EMC Compliance	: CE / EMC certified
Safety Compliance	: CE / LVD certified
Environment Compliance	: RoHS3, Reach & WEEE
Operating Temperature	: -5 to 60 °C
Storage Temperature	: -25 to 65 °C
Operating Altitude	: 0 to 2,000 m
Storage Altitude	: 0 to 15,000 m
Humidity	: 8 to 95% RH, non-condensing