



Circuit Details : UK # 1 - 8

230V model	Inlet x 2	Cordset x 2	16A MCB
ATS-H8UK-16A-WS_EN ATS-H8UK-16A-BS_EN	16 Amp IEC 60309 2P+E	3M 1.5mm sq. H05V V-F	1

230V model	Inlet x 2	Cordset x 2	16A MCB
ATS-H8UK-16A-WS_C20 ATS-H8UK-16A-BS_C20	16 Amp IEC320 C20	3M 1.5mm sq. H05V V-F	1

230V model	Inlet x 2	Cordset x 2	13A MCB
ATS-H8UK-13A-WS_BS ATS-H8UK-13A-BS_BS	13 Amp BS1363 (fused)	3M 1.5mm sq. H05V V-F	1

230V model	Inlet x 2	Cordset x 2	10A MCB
ATS-H8UK-10A-WS_C14 ATS-H8UK-10A-BS_C14	10 Amp IEC320 C14	3M 1.5mm sq. H05V V-F	1



Specification				Meter Features		WS ATS	BS ATS	EMC Certificates	
Operating Temperature	:	-5 to 60 °C	Nominal input volt.	:	230V	Local Display	:	2.0" color touch LCD	3-digit LED
Storage Temperature	:	-25 to 65 °C	Acceptable input volt.	:	±10% nominal	Bank Measurement	:	Volt, Amp, kWh & Power Factor	Same as WS
Operating Altitude	:	0 to 2,000 m	Input frequency	:	50 / 60Hz	Outlet Control	:	Outlet Switch ON / OFF	Same as WS
Storage Altitude	:	0 to 15,000 m	Transfer time	:	10 ms typical	Accuracy	:	±1% Billing-grade	Same as WS
Humidity (non-condensing)	:	8 to 95% RH	Electrical endurance	:	1 x 10 ⁵ operations	IP Access	:	Embedded IP with Gigabit Ethernet port	Same as WS
			Power consumption	:	Approx. 20W			Enterprise IP Authentication, LDAPv3 / LDAPS, Active Directory®, RADIUS protocol	Same as WS
						SNMP	:	V2 / V3 & GUI	Same as WS
Chassis Material / Color				:	Steel / Black				
Product Dimension				:	442W x 300D x 43.5H (mm)				
Packing Dimension				:	500W x 540D x 150H (mm)				
Net / Gross Weight				:	5.7 kg / 6.2 kg				