

Chassis Color	Code
 Black	1
 White	2
 Red	3
 Blue	4
 Green	5
 Orange	6
 Yellow	7
 Purple	8

Standard color : Black

30A model	V12L13/4L19-30A-MSi/CR_L630/3B-1	MSi PDU	Outlet switching & monitoring	30A Inlet NEMA L6-30P  10ft Cordset 3W 10AWG UL SJT	Circuit A : 12A max., C13 #1-6 + C19 #13-14 Circuit B : 12A max., C13 #7-12 + C19 #15-16 Outlet with LED only for Outlet switching PDU
	V12L13/4L19-30A-MS /CR_L630/3B-1	MS PDU	Outlet switching		
	V12L13/4L19-30A-Mi /CR_L630/3B-1	Mi PDU	Outlet monitoring		
	V12L13/4L19-30A-M /CR_L630/3B-1	M PDU	Circuit monitoring		
20A model	V12L13/4L19-20A-MSi/CR_L620/3B-1	MSi PDU	Outlet switching & monitoring	20A Inlet NEMA L6-20P  10ft Cordset 3W 12AWG UL SJT	Circuit : 16A max., C13 #1-12 + C19 #13-16 Outlet with LED only for Outlet switching PDU
	V12L13/4L19-20A-MS /CR_L620/3B-1	MS PDU	Outlet switching		
	V12L13/4L19-20A-Mi /CR_L620/3B-1	Mi PDU	Outlet monitoring		
	V12L13/4L19-20A-M /CR_L620/3B-1	M PDU	Circuit monitoring		

Slide Lock Outlet	
Worldwide Patented	
	Black
	Grey
	White
	Red
	Blue
	Green
Standard color Single circuit : Black Dual circuit : Black / Grey	




Dimension & Weight

MSi / MS / Mi PDU	
Product Dimension	: 2.2W x 2.7D x 41.3H (inch)
Packing Dimension (2-in-1)	: 4.3W x 10.6D x 54.8H (inch)
Net / Gross Weight	: 13.3 lb / 15.1 lb

M PDU	
Product Dimension	: 2.2W x 2.2D x 41.3H (inch)
Packing Dimension (2-in-1)	: 4.3W x 10.6D x 54.8H (inch)
Net / Gross Weight	: 10.9 lb / 12.6 lb

Specification

Operating Temperature	: -5 to 60 °C
Storage Temperature	: -25 to 65 °C
Operating Altitude	: 0 to 2,000 m
Storage Altitude	: 0 to 15,000 m
Humidity (non-condensing)	: 8 to 95% RH
Chassis Material / Color	: Steel / Black



Meter Features	MSi PDU	MS PDU	Mi PDU	M PDU
Local Display	: Field replaceable 2.8" color LCD with touchscreen	Same	Same	Same
Bank Measurement	: Current (A), Energy (kWh), Voltage (V) & Power factor	Same	Same	Same
Outlet Measurement	: Current (A), Energy (kWh)	✗	Same	✗
Outlet Control	: Outlet Switch ON / OFF	Same	✗	✗
Accuracy	: ±1% Billing-grade	Same	Same	Same
IP connection	: via IP dongle or IP PDU on first level	Same	Same	Same
Cascade	: Up to 32 PDU under single IP address	Same	Same	Same
USB-C port x 1	: Support backup power against meter power failure	Same	Same	Same
Sensor Port x 4	: Temp. Sensor / Temp. + Humid. Sensor / Door Sensor	Same	Same	Same
IP dongle (option)				
- Dual LAN Network Failover				
- 10/100 Ethernet & Gigabit Ethernet standard				
- Enterprise IP Authentication, LDAPv3 / LDAPS, Active Directory®, RADIUS protocol				

EMC Certificates	
FCC	: FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 7
Safety Certificates	
CB	: IEC 62368-1:2014
UL-US	: UL 62368-1, 2nd Ed., Issue Date: 2014-12-01
UL-CA	: CSA C22.2 No. 62368-1-14, 2nd Ed., Issue Date: 2014-12-01
Environment : RoHS, Reach & WEEE	