



Chassis Color	Code
Black	1
White	2
Red	3
Blue	4
Green	5
Orange	6
Yellow	7
Purple	8

Standard color : Black

30A model	V12L13/4L19-30A-MK/CR_L630/3B-1	30A Inlet NEMA L6-30P 10ft Cordset 3W 10AWG UL SJT	Circuit A : 12A max., C13 #1-6 + C19 #13-14 Circuit B : 12A max., C13 #7-12 + C19 #15-16
20A model	V12L13/4L19-20A-MK/CR_L620/3B-1	20A Inlet NEMA L6-20P 10ft Cordset 3W 12AWG UL SJT	Circuit : 16A max., C13 #1-12 + C19 #13-16

Slide Lock Outlet
Worldwide Patented
Black
Grey
White
Red
Blue
Green

Standard color
Single circuit : Black
Dual circuit : Black / Grey



Dimension & Weight	
Product Dimension	: 2.2W x 2.2D x 41.3H (inch)
Packing Dimension (2-in-1)	: 4.3W x 10.6D x 54.8H (inch)
Net / Gross Weight	: 10.8 lb / 13.3 lb

Specification	
Operating Temperature	: -5 to 60 °C
Storage Temperature	: -25 to 65 °C
Operating Altitude	: 0 to 2,000 m
Storage Altitude	: 0 to 15,000 m
Humidity (non-condensing)	: 8 to 95% RH
Chassis Material / Color	: Steel / Black

Meter Features



Local Display	: Hotswappable 1.8" Color LCD
Strip level	: Current (A), Phase Voltage (V), Energy (kW), Power Factor & Frequency (Hz)
Accuracy	: Billing Grade +/-1%

Safety Certificates

CB	: IEC 62368-1:2018
UL-US	: UL 62368-1, 3rd Ed, 2021-10-22
UL-CA	: CAN/ CSA C22.2 No. 62368-1:19, 3rd Ed, 2021-10-22

EMC Certificates

FCC	: FCC 47 CFR Part 15 Subpart B
-----	--------------------------------

Environment : RoHS, Reach & WEEE