


unit : inch



Chassis Color	Code
Black	1
White	2
Red	3
Blue	4
Green	5
Orange	6
Yellow	7
Purple	8

Standard color: Black

30A model	V12L19-30A-MD/CR_L630/3B-1	MD PDU Local metered	30A Inlet NEMA L6-30P	Circuit A : 12A max., C19 #1-6 Circuit B : 12A max., C19 #7-12
	V12L19-30A- CR_L630/3B-1	Basic PDU	10ft Cordset 3W 10AWG UL SJT	
20A model	V12L19-20A-MD/CR_L620/3B-1	MD PDU Local metered	20A Inlet NEMA L6-20P	Circuit : 16A max., C19 #1-12
	V12L19-20A- CR_L620/3B-1	Basic PDU	10ft Cordset 3W 12AWG UL SJT	

Slide Lock Outlet
Worldwide Patented
Black
Grey
White
Red
Blue
Green

Standard color
Single circuit : Black
Dual circuit : Black / Grey



Dimension & Weight	Meter Features	MD PDU	Basic PDU	EMC Certificates
Product Dimension : 2.2W x 2.2D x 31.5H (inch) Packing Dimension (2-in-1) : 4.3W x 10.6D x 43.0H (inch) Net / Gross Weight : 9.6 lb / 11.3 lb		Local Display : 3-digit LED ammeter measuring input load current	✗	FCC : FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 7
		Measurement : Current (A)	✗	Safety Certificates CB : IEC 62368-1:2014 UL-US : UL 62368-1, 2nd Ed., Issue Date: 2014-12-01 UL-CA : CSA C22.2 No. 62368-1-14, 2nd Ed., Issue Date: 2014-12-01
		Accuracy : ± (3% of the reading + 5 digits) RMS	✗	Environment : RoHS, Reach & WEEE
Specification				
Operating Temperature : -5 to 60 °C Storage Temperature : -25 to 65 °C Operating Altitude : 0 to 2,000 m Storage Altitude : 0 to 15,000 m Humidity (non-condensing) : 8 to 95% RH Chassis Material / Color : Steel / Black				