



Chassis Color	Code
Black	1
White	2
Red	3
Blue	4
Green	5
Orange	6
Yellow	7
Purple	8

Standard color : Black

30A model	V18L13/6L19-30A-MSi/CR_L630/3B-1	MSi PDU	Outlet switching & monitoring	30A Inlet NEMA L6-30P 10ft Cordset 3W 10AWG UL SJT	Circuit A : 12A max., C13 #1-9 + C19 #19-21 Circuit B : 12A max., C13 #10-18 + C19 #22-24 Outlet with LED only for Outlet switching PDU
	V18L13/6L19-30A-MS /CR_L630/3B-1	MS PDU	Outlet switching		
	V18L13/6L19-30A-Mi /CR_L630/3B-1	Mi PDU	Outlet monitoring		
	V18L13/6L19-30A-M /CR_L630/3B-1	M PDU	Circuit monitoring		
20A model	V18L13/6L19-20A-MSi/CR_L620/3B-1	MSi PDU	Outlet switching & monitoring	20A Inlet NEMA L6-20P 10ft Cordset 3W 12AWG UL SJT	Circuit : 16A max., C13 #1-18 + C19 #19-24 Outlet with LED only for Outlet switching PDU
	V18L13/6L19-20A-MS /CR_L620/3B-1	MS PDU	Outlet switching		
	V18L13/6L19-20A-Mi /CR_L620/3B-1	Mi PDU	Outlet monitoring		
	V18L13/6L19-20A-M /CR_L620/3B-1	M PDU	Circuit monitoring		

Slide Lock Outlet
Worldwide Patented

	Black
	Grey
	White
	Red
	Blue
	Green

Standard color
Single circuit : Black
Dual circuit : Black / Grey**Dimension & Weight****MSi / MS / Mi PDU**

Product Dimension	: 2.2W x 2.7D x 57.1H (inch)
Packing Dimension (2-in-1)	: 4.3W x 10.6D x 70.1H (inch)
Net / Gross Weight	: 16.9 lb / 19.7 lb

M PDU

Product Dimension	: 2.2W x 2.2D x 57.1H (inch)
Packing Dimension (2-in-1)	: 4.3W x 10.6D x 70.1H (inch)
Net / Gross Weight	: 13.7 lb / 16.5 lb

Specification

Operating Temperature	: -5 to 60 °C
Storage Temperature	: -25 to 65 °C
Operating Altitude	: 0 to 2,000 m
Storage Altitude	: 0 to 15,000 m
Humidity (non-condensing)	: 8 to 95% RH
Chassis Material / Color	: Steel / Black

Meter Features**MSi PDU**

Local Display	: Field replaceable 2.8" color LCD with touchscreen
Bank Measurement	: Current (A), Energy (kWh), Voltage (V) & Power factor
Outlet Measurement	: Current (A), Energy (kWh)
Outlet Control	: Outlet Switch ON / OFF
Accuracy	: ±1% Billing-grade
IP connection	: via IP dongle or IP PDU on first level
Cascade	: Up to 32 PDU under single IP address
USB-C port x 1	: Support backup power against meter power failure
Sensor Port x 4	: Temp. Sensor / Temp. + Humid. Sensor / Door Sensor

IP dongle (option)

- Dual LAN Network Failover
- 10/100 Ethernet & Gigabit Ethernet standard
- Enterprise IP Authentication, LDAPv3 / LDAPS, Active Directory®, RADIUS protocol

MS PDU**Mi PDU****M PDU**

Same	Same	Same
Same	Same	Same
✗	Same	✗
Same	✗	✗
Same	Same	Same
Same	Same	Same
Same	Same	Same
Same	Same	Same
Same	Same	Same

EMC Certificates

FCC : FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 7

Safety Certificates

CB	: IEC 62368-1:2014
UL-US	: UL 62368-1, 2nd Ed., Issue Date: 2014-12-01
UL-CA	: CSA C22.2 No. 62368-1-14, 2nd Ed., Issue Date: 2014-12-01

Environment : RoHS, Reach & WEEE