


unit : inch



PDU Feed	Code
Bottom	B
Top	T

Slide-lock outlet : C13 x 18 + C19 x 6

Circuit Protection	Code
Hydraulic MCB	CR
Resettable Fuse	F

Chassis Color	Code
Black	1
White	2
Red	3
Blue	4
Green	5
Orange	6
Yellow	7
Purple	8

Standard color: Black

30A model	Code	Function	30A Inlet NEMA L6-30P 10ft Cordset 3W 10AWG UL SJT	Circuit A : 12A max., C13 #1-9 + C19 #19-21 Circuit B : 12A max., C13 #10-18 + C19 #22-24
	V18L13/6L19-30A-ZSi/CR_L630/3B-1	ZSi PDU		
V18L13/6L19-30A-ZS /CR_L630/3B-1	ZS PDU	Outlet switching		
V18L13/6L19-30A-Zi /CR_L630/3B-1	Zi PDU	Outlet monitoring		
V18L13/6L19-30A-Z /CR_L630/3B-1	Z PDU	Circuit monitoring		
Outlet with LED only for Outlet switching PDU				

20A model	Code	Function	20A Inlet NEMA L6-20P 10ft Cordset 3W 12AWG UL SJT	Circuit : 16A max., C13 #1-18 + C19 #19-24
	V18L13/6L19-20A-ZSi/CR_L620/3B-1	ZSi PDU		
V18L13/6L19-20A-ZS /CR_L620/3B-1	ZS PDU	Outlet switching		
V18L13/6L19-20A-Zi /CR_L620/3B-1	Zi PDU	Outlet monitoring		
V18L13/6L19-20A-Z /CR_L620/3B-1	Z PDU	Circuit monitoring		
Outlet with LED only for Outlet switching PDU				


Slide Lock Outlet	
Worldwide Patented	
	Black
	Grey
	White
	Red
	Blue
	Green

Standard color : Black
Single circuit : Black
Dual circuit : Black / Grey



Dimension & Weight	
ZSi / ZS / Zi PDU	
Product Dimension	: 2.2W x 2.7D x 57.1H (inch)
Packing Dimension (2-in-1)	: 4.3W x 10.6D x 70.1H (inch)
Net / Gross Weight	: 16.9 lb / 19.7 lb
Z PDU	
Product Dimension	: 2.2W x 2.2D x 57.1H (inch)
Packing Dimension (2-in-1)	: 4.3W x 10.6D x 70.1H (inch)
Net / Gross Weight	: 13.7 lb / 16.5 lb
Specification	
Operating Temperature	: -5 to 60 °C
Storage Temperature	: -25 to 65 °C
Operating Altitude	: 0 to 2,000 m
Storage Altitude	: 0 to 15,000 m
Humidity (non-condensing)	: 8 to 95% RH
Chassis Material / Color	: Steel / Black

Meter Features	ZSi PDU	ZS PDU	Zi PDU	Z PDU
Local Display : Field replaceable 2.8" color LCD with touchscreen	✓	✓	✓	✓
Bank Measurement : Current (A), Energy (kWh), Voltage (V) & Power factor	✓	✓	✓	✓
Outlet Measurement : Current (A), Energy (kWh) (Zi & ZSi only)	✓	✗	✓	✗
Outlet Control : Outlet Switch ON / OFF (ZS & ZSi only)	✓	✓	✗	✗
Accuracy : ±0.5% Billing-grade	✓	✓	✓	✓
IP Access : Embedded Dual Gigabit LAN IP	✓	✓	✓	✓
Dual LAN Network Failover	✓	✓	✓	✓
Enterprise IP Authentication, LDAPv3 / LDAPS	✓	✓	✓	✓
Active Directory®, RADIUS, 802.1x	✓	✓	✓	✓
Protocol : SNMP V2 V3, Web GUI, Modbus/TCP, RestAPI, LUA	✓	✓	✓	✓
Cascade : Up to 32 PDU under single IP address	✓	✓	✓	✓
Console port x 1 : PDU configuration	✓	✓	✓	✓
USB-C port x 1 : Wi-Fi connection, firmware update, backup power for meter	✓	✓	✓	✓
Sensor Port x 1 : Temp. Sensor / Temp. + Humid. Sensor / Door Sensor (support daisy chain sensors up to 4)	✓	✓	✓	✓



Safety Certificates	
CB	: IEC 62368-1:2018
UL-US	: UL 62368-1, 3rd Ed, 2021-10-22
UL-CA	: CAN/ CSA C22.2 No. 62368-1:19, 3rd Ed, 2021-10-22
EMC Certificates	
FCC	: FCC 47 CFR Part 15 Subpart B
Environment : RoHS, Reach & WEEE	