



Chassis Color	Code
Black	1
White	2
Red	3
Blue	4
Green	5
Orange	6
Yellow	7
Purple	8

Standard color : Black

30A model	V20L13/4X19-30A-MD/CR_L630/3B-1	MD PDU Local metered	30A Inlet NEMA L6-30P 10ft Cordset 3W 10AWG UL SJT	Circuit A : 12A max., C13 #1-10 + C13/C19 #21-22 Circuit B : 12A max., C13 #11-20 + C13/C19 #23-24
	V20L13/4X19-30A- CR_L630/3B-1	Basic PDU		
20A model	V20L13/4X19-20A-MD/CR_L620/3B-1	MD PDU Local metered	20A Inlet NEMA L6-20P 10ft Cordset 3W 12AWG UL SJT	Circuit : 16A max., C13 #1-20 + C13/C19 #21-24
	V20L13/4X19-20A- CR_L620/3B-1	Basic PDU		

Slide Lock Outlet
Worldwide Patented
Black
Grey
White
Red
Blue
Green

Standard color
Single circuit : Black
Dual circuit : Black / Grey



Dimension & Weight	
Product Dimension	: 2.2W x 2.2D x 47.2H (inch)
Packing Dimension (2-in-1)	: 4.3W x 10.6D x 70.6H (inch)
Net / Gross Weight	: 12 lb / 14.8 lb

Specification	
Operating Temperature	: -5 to 60 °C
Storage Temperature	: -25 to 65 °C
Operating Altitude	: 0 to 2,000 m
Storage Altitude	: 0 to 15,000 m
Humidity (non-condensing)	: 8 to 95% RH
Chassis Material / Color	: Steel / Black

Meter Features	MD PDU	Basic PDU
Local Display	: 3-digit LED ammeter measuring input load current	✗
Measurement	: Current (A)	✗
Accuracy	: ± (3% of the reading + 5 digits) RMS	✗

EMC Certificates	
FCC	: FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 7

Safety Certificates	
CB	: IEC 62368-1:2014
UL-US	: UL 62368-1, 2nd Ed., Issue Date: 2014-12-01
UL-CA	: CSA C22.2 No. 62368-1-14, 2nd Ed., Issue Date: 2014-12-01

Environment	
	: RoHS, Reach & WEEE