

Chassis Color	Code
 Black	1
 White	2
 Red	3
 Blue	4
 Green	5
 Orange	6
 Yellow	7
 Purple	8

Standard color : Black

30A model	V24L13-30A-MSi/CR_L630/3B-1	MSi PDU	Outlet switching & monitoring	30A Inlet NEMA L6-30P  10ft Cordset 3W 10AWG UL SJT	Circuit A : 12A max., C13 #1-12 Circuit B : 12A max., C13 #13-24 Outlet with LED only for Outlet switching PDU
	V24L13-30A-MS /CR_L630/3B-1	MS PDU	Outlet switching		
	V24L13-30A-Mi /CR_L630/3B-1	Mi PDU	Outlet monitoring		
	V24L13-30A-M /CR_L630/3B-1	M PDU	Circuit monitoring		
20A model	V24L13-20A-MSi/CR_L620/3B-1	MSi PDU	Outlet switching & monitoring	20A Inlet NEMA L6-20P  10ft Cordset 3W 12AWG UL SJT	Circuit : 16A max., C13 #1-24 Outlet with LED only for Outlet switching PDU
	V24L13-20A-MS /CR_L620/3B-1	MS PDU	Outlet switching		
	V24L13-20A-Mi /CR_L620/3B-1	Mi PDU	Outlet monitoring		
	V24L13-20A-M /CR_L620/3B-1	M PDU	Circuit monitoring		

Slide Lock Outlet
Worldwide Patented

	Black
	Grey
	White
	Red
	Blue
	Green

Standard color
Single circuit : Black
Dual circuit : Black / Grey**Dimension & Weight****MSi / MS / Mi PDU**


Product Dimension	: 2.2W x 2.7D x 51.2H (inch)
Packing Dimension (2-in-1)	: 4.3W x 10.6D x 70.1H (inch)
Net / Gross Weight	: 15.9 lb / 18.3 lb

M PDU

Product Dimension	: 2.2W x 2.2D x 51.2H (inch)
Packing Dimension (2-in-1)	: 4.3W x 10.6D x 70.1H (inch)
Net / Gross Weight	: 12.7 lb / 15.1 lb

Specification

Operating Temperature	: -5 to 60 °C
Storage Temperature	: -25 to 65 °C
Operating Altitude	: 0 to 2,000 m
Storage Altitude	: 0 to 15,000 m
Humidity (non-condensing)	: 8 to 95% RH
Chassis Material / Color	: Steel / Black

Meter Features

	MSi PDU	MS PDU	Mi PDU	M PDU
Local Display	: Field replaceable 2.8" color LCD with touchscreen	✓	✓	✓
Bank Measurement	: Current (A), Energy (kWh), Voltage (V) & Power factor	✓	✓	✓
Outlet Measurement	: Current (A), Energy (kWh)	✓	✗	✗
Outlet Control	: Outlet Switch ON / OFF	✓	✓	✗
Accuracy	: ±0.5% Billing-grade	✓	✓	✓
IP connection	: via IP dongle or IP PDU on first level	✓	✓	✓
Cascade	: Up to 32 PDU under single IP address	✓	✓	✓
USB-C port x 1	: Backup power against meter power failure	✓	✓	✓
Sensor Port x 4	: Temp / Temp + Humid / Door / Smoke / Water Sensor	✓	✓	✓

IP dongle (option)

- Embedded Dual Gigabit LAN IP
- Dual LAN Network Failover
- Enterprise IP Authentication, LDAPv3 / LDAPS
- Active Directory®, RADIUS, 802.1x
- SNMP V2 V3, Web GUI, Modbus/TCP, RestAPI, LUA
- Wi-Fi connection via USB-C port

Safety Certificates

CB	: IEC 62368-1:2018
UL-US	: UL 62368-1, 3rd Ed, 2021-10-22
UL-CA	: CAN/ CSA C22.2 No. 62368-1:19, 3rd Ed, 2021-10-22

EMC Certificates

FCC	: FCC 47 CFR Part 15 Subpart B
-----	--------------------------------

Environment : RoHS, Reach & WEEE