



Chassis Color	Code
Black	1
White	2
Red	3
Blue	4
Green	5
Orange	6
Yellow	7
Purple	8

Standard color: Black

30A model	V24X19-30A-MD/CR_L630/3B-1	MD PDU Local metered	30A Inlet NEMA L6-30P	Circuit A : 12A max., C13/C19 #1-12 Circuit B : 12A max., C13/C19 #13-24
	V24X19-30A- CR_L630/3B-1	Basic PDU	10ft Cordset 3W 10AWG UL SJT	
20A model	V24X19-20A-MD/CR_L620/3B-1	MD PDU Local metered	20A Inlet NEMA L6-20P	Circuit : 16A max., C13/C19 #1-24
	V24X19-20A- CR_L620/3B-1	Basic PDU	10ft Cordset 3W 12AWG UL SJT	

Slide Lock Outlet	
Worldwide Patented	
	Black
	Grey
	White
	Red
	Blue
	Green

Standard color
Single circuit : Black
Dual circuit : Black / Grey



Dimension & Weight

Product Dimension : 2.2W x 2.2D x 47.2H (inch)
Packing Dimension (2-in-1) : 4.3W x 10.6D x 70.6H (inch)
Net / Gross Weight : 12.4 lb / 15.2 lb

Specification

Operating Temperature : -5 to 60 °C
Storage Temperature : -25 to 65 °C
Operating Altitude : 0 to 2,000 m
Storage Altitude : 0 to 15,000 m
Humidity (non-condensing) : 8 to 95% RH
Chassis Material / Color : Steel / Black

Meter Features MD PDU



Local Display : 3-digit LED ammeter measuring input load current
Measurement : Current (A)
Accuracy : ± (3% of the reading + 5 digits) RMS

Basic PDU

✗
✗
✗

EMC Certificates

FCC : FCC 47 CFR Part 15 Subpart B, ICES-003 Issue 7

Safety Certificates

CB : IEC 62368-1:2014
UL-US : UL 62368-1, 2nd Ed., Issue Date: 2014-12-01
UL-CA : CSA C22.2 No. 62368-1-14, 2nd Ed., Issue Date: 2014-12-01

Environment : RoHS, Reach & WEEE