

unit : inch

(T) Top feed



2.2

Serial meter |

1 - 18

19 - 36

Bottom feed (B)



Slide-lock outlet : C13/C19 x 36

PDU Feed	Code
Bottom	B
Top	T

Circuit Protection	Code
Hydraulic MCB	CR
Resettable Fuse	F

Chassis Color	Code
Black	1
White	2
Red	3
Blue	4
Green	5
Orange	6
Yellow	7
Purple	8

Standard color : Black

30A model	V36X19-30A-MSi/CR_L630/3B-1	MSi PDU Outlet switching & monitoring	30A Inlet NEMA L6-30P 10ft Cordset 3W 10AWG UL SJT	Circuit A : 12A max., C13/C19 #1-18 Circuit B : 12A max., C13/C19 #19-36 Outlet with LED only for Outlet switching PDU
	V36X19-30A-MS /CR_L630/3B-1	MS PDU Outlet switching		
	V36X19-30A-Mi /CR_L630/3B-1	Mi PDU Outlet monitoring		
	V36X19-30A-M /CR_L630/3B-1	M PDU Circuit monitoring		
20A model	V36X19-20A-MSi/CR_L620/3B-1	MSi PDU Outlet switching & monitoring	20A Inlet NEMA L6-20P 10ft Cordset 3W 12AWG UL SJT	Circuit : 16A max., C13/C19 #1-36 Outlet with LED only for Outlet switching PDU
	V36X19-20A-MS /CR_L620/3B-1	MS PDU Outlet switching		
	V36X19-20A-Mi /CR_L620/3B-1	Mi PDU Outlet monitoring		
	V36X19-20A-M /CR_L620/3B-1	M PDU Circuit monitoring		

Slide Lock Outlet
Worldwide Patented

	Black
	Grey
	White
	Red
	Blue
	Green

Standard color
Single circuit : Black
Dual circuit : Black / Grey

REACH



Dimension & Weight

MSi / MS / Mi PDU

Product Dimension	: 2.2W x 2.7D x 74.0H (inch)
Packing Dimension (2-in-1)	: 4.3W x 10.6D x 85.4H (inch)
Net / Gross Weight	: 21.4 lb / 24.5 lb


M PDU

Product Dimension	: 2.2W x 2.2D x 74.0H (inch)
Packing Dimension (2-in-1)	: 4.3W x 10.6D x 85.4H (inch)
Net / Gross Weight	: 17.0 lb / 20.1 lb

Specification

Operating Temperature	: -5 to 60 °C
Storage Temperature	: -25 to 65 °C
Operating Altitude	: 0 to 2,000 m
Storage Altitude	: 0 to 15,000 m
Humidity (non-condensing)	: 8 to 95% RH
Chassis Material / Color	: Steel / Black

Meter Features



	MSi PDU	MS PDU	Mi PDU	M PDU
Local Display	✓	✓	✓	✓
Bank Measurement	✓	✓	✓	✓
Outlet Measurement	✓	✗	✓	✗
Outlet Control	✓	✓	✗	✗
Accuracy	✓	✓	✓	✓
IP connection	✓	✓	✓	✓
Cascade	✓	✓	✓	✓
USB-C port x 1	✓	✓	✓	✓
Sensor Port x 4	✓	✓	✓	✓

IP dongle (option)

- Embedded Dual Gigabit LAN IP
- Dual LAN Network Failover
- Enterprise IP Authentication, LDAPv3 / LDAPS
- Active Directory®, RADIUS, 802.1x
- SNMP V2 V3, Web GUI, Modbus/TCP, RestAPI, LUA
- Wi-Fi connection via USB-C port

Safety Certificates

CB	: IEC 62368-1:2018
UL-US	: UL 62368-1, 3rd Ed, 2021-10-22
UL-CA	: CAN/ CSA C22.2 No. 62368-1:19, 3rd Ed, 2021-10-22

EMC Certificates

FCC	: FCC 47 CFR Part 15 Subpart B
-----	--------------------------------

Environment : RoHS, Reach & WEEE